



## High purity microfine natural grade graphite flakes / powder

### **Benefits**

- Very high purity graphite with minimum ash content.
- Excellent adhesion on metal substrates without any special treatment.
- Eliminates galling, seizure and stick-slip.
- Reduces wear and friction by forming a film that eliminates metal to metal contact.
- Withstands very high temperatures.
- Reduces damage and maintenance costs by providing more effective lubrication.

### **Applications**

- As an additive to conventional oils and greases for increasing extreme pressure carrying capacity.
- As a release agent for pressure die casting.
- As a glass molding lubricant.
- As a high temperature conveyor chain lubricant.
- For manufacture of lead pencils, carbon brushes, electrodes.
- As a parting agent for gaskets and seals at high temperatures.
- As a dry film lubricant for bearings, cams, slides, roller chains, guides.
- As an extreme pressure lubricant for hinges, threaded spindles, cableways and gears.
- As a metal working lubricant additive for bending, wire drawing, extrusion, forging, deep drawing.

### **Properties**

Type	Powder
Appearance	Free flowing
Color	Black
Odor	Nil
Particle size	1-5 microns
Ash content	10 to 12 % max
Moisture content	1 % max
Fixed carbon content	87 %

### **Methods of Application**

By tumbling, burnishing, polishing or rubbing. Can also be dispersed in solvents to aid application.

## Technical Information

# GP 7188

## Powder

### **Available Packaging**

- 1kg container

### **General**

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

### **Disposal**

All used and unused product should be disposed of in accordance with state regulations.

### **Shelf Life**

36 months from date of manufacture in sealed condition

### **Handling**

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

### **Limited Warranty**

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

---

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA

Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com

MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals.

® Registered trademark of ASV Multichemie Private Limited, INDIA.

THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Distributed by: