



Technical Information

KL 2000 SD

High Viscosity Synthetic Chain Oil

Product Description

ASV® KL 2000 SD is a fully synthetic formulation developed primarily for lubrication of chains, gears, wire ropes, cams operating under adverse conditions of high temperatures, high loadings, wear and friction.

It exhibits excellent resistance to oxidation especially at elevated temperatures, has a very low evaporation rate and is fully resistant to water, water washout, steam & humid environments.

Applications

For lubrication of all types of chains working under severe operating conditions of high temperatures, excessive friction, high loads, water and corrosive presence.

Benefits

- Friction reducing organic additives reduce wear and eliminate metal-to-metal contact
- Does not get washed off by hot or cold water
- Excellent extreme pressure properties
- Extremely low evaporation rate at high temperatures
- Due to its absolute synthetic formulation, there is no carbon or resinous deposit even at high temperatures
- Minimized deposit formation reduces cost related to chain cleaning such as labor, production loss and downtime
- Lower evaporation rate reduces consumption and extends relubrication periods thereby reducing lubricant consumption
- Provides superior lubrication and protection even when subjected to high temperatures and humid conditions
- Due to superior lubrication, friction and power requirements are reduced resulting in both lubricant as well as energy savings
- Cost savings due to reduction of premature wearing out of parts and replacements are also greatly increased

Directions for Use (Bulk)

For optimal lubrication and adhesion, clean and degrease the surface of all previous residues, lubricants or contaminants with ASV® CS 50 heavy duty degreaser. Apply to clean surface by regular oiling methods i.e. by brushing, spraying, dipping or drop feed oiling mechanisms. Do not mix or dilute with other oils or grease. Replace cap after use.

Directions for Use (Aerosol)

Clean and degrease the chain completely off old protective coatings, oil, grease or dirt residues. Apply from all sides and allow 10-15 minutes for the lubricant to penetrate to all points and solvents to evaporate before resuming operations.

Caution

Contains flammable propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

Technical Information

KL 2000 SD

High Viscosity Synthetic Chain Oil

Technical Properties

| Property | Test Method | Value |
|-------------------------------|-------------|--|
| Type | In house | Synthetic oil with EP additives and inhibitors for oxidation & corrosion |
| Appearance | Visual | Highly adhesive oily liquid |
| Color | Visual | Greenish yellow |
| Base Oil | In house | Synthetic |
| Viscosity at 40°C | ASTM D 445 | Approx. 2000 mm ² /s |
| Viscosity at 100°C | ASTM D 445 | Approx. 125 mm ² /s |
| Flash point | ASTM D 92 | +250 °C |
| Service Temperature Range, °C | In house | 0 to +200 |
| Propellant (aerosol only) | In house | Non CFC |

*of active ingredients

Available Packaging

- 500 ml aerosol spray
- 5 liter container

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Shelf Life

Bulk - 36 months from date of manufacture in sealed condition
Aerosol - 24 months from date of manufacture

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA

Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com

MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals.

® Registered trademark of ASV Multichemie Private Limited, INDIA.

THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Distributed by: