



## Technical Information

# KL 6460

## Chain Oil

### Applications

Lubrication of all chains, clips, bearings in industrial machinery

### Benefits

- Extremely wide service temperature range from -10°C to +150°C
- Very good extreme pressure properties enhance load carrying abilities and reduces frictional wear
- Extremely low evaporation rate at high temperatures
- Minimized deposit formation reduces cost related to chain cleaning such as labor, production loss and downtime
- Lower evaporation rate reduces consumption and allows for extension of lubrication periods thereby cutting down on lubrication costs
- Provides superior lubrication and protection even when subjected to high temperatures and humid conditions
- Due to superior lubrication, power requirements are reduced resulting in both lubricant as well as energy savings
- Cost savings due to reduction of parts premature wearing out and replacements are also greatly increased
- Good adhesive properties and water resistant

### Directions for Use

Use as supplied. Never dilute or mix with other oil or grease. For optimal lubrication and adhesion, clean and degrease the surface of all previous residues, lubricants or contaminants with ASV® CS 50 heavy duty degreaser.

Apply to clean surface by regular oiling methods i.e. by brushing, spraying, dipping or drop feed oiling mechanisms. Allow time for lubricant to penetrate and excess lubricant to drip off before restarting operations.

For new chains: Thoroughly clean prior to applying this lubricant. It is recommended to keep new chains dipped in the lubricant for 30 minutes to ensure complete penetration to all innermost points.

Avoid excessive use. Use as per instructions laid down in manufacturers manual. Replace cap after use.

## Technical Information

# KL 6460

## Chain Oil

### Technical Properties

Property	Value	Method
Appearance	Oily liquid	Visual
Color	Dark yellow	Visual
Viscosity at 40°C, mm <sup>2</sup> /s	400-460	ASTM D 445
ISO VG	460	
Density, g/cc	0.92-0.98	
Flash point, °C	+ 250 min	ASTM D 92
Pour point, °C	- 10	ASTM D 97
Service temperature range, °C	- 10 to +150	

1. Minor color variation of the same product but of different batches could be possible. However the lubrication values remain unchanged.

### Available Packaging

- 5 liter & 30 liter container

### General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

### Disposal

All used and unused product should be disposed of in accordance with state regulations.

### Shelf Life

36 months from date of manufacture in sealed condition

### Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

### Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA

Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com

MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals.

® Registered trademark of ASV Multichemie Private Limited, INDIA.

THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Distributed by: