



## Silicone Free Mold Release

### ***Product Description***

ASV® 4299 is a specially formulated, paintable mold release agent that is ideal for all types of plastics where decorating is required after molding.

It does not interfere with post finishing processes and is designed for quick, clean releases on thermosets as well as thermoplastics. It allows easy removal of parts from molds and improves surface finish of molded part.

ASV® 4299 is non staining, odorless and does not contain any ozone depleting chemicals or CFC's.

### ***Applications***

Recommended for use on compression molding gaskets, toy and furniture manufacturing, urethanes, epoxy resins, polyesters, and polystyrenes.

### ***Benefits***

- Excellent for parts requiring post molding finishing
- Prevents sticking & increases life of dies & molds
- Provides maximum efficiency & economy
- Fewer rejects & more production
- Improves product surface finish
- Non staining & non corrosive

### ***Directions for Use***

Shake can well before using. Hold can 10-12" from surface and spray a thin, light coating. Do not spray directly on plastics.

### ***Directions for Use***

Contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces.

Technical Information

**4299**

Silicone Free Mold Release

**Technical Properties**

Property	Value
Type	Mold release agent
Appearance	Oily liquid
Color	Water white
Odor	Odorless
Product	Non silicone
Specific Gravity	Less than 1.00 gm/cc
Flash Point	-18°C (aerosol)
Boiling Point	ND
Vapor Pressure (air=1)	ND
Solubility	Slightly soluble
Temperature Range ° C	Up to +250°C
Propellant	Non CFC

\* of active ingredients

**Available Packaging**

- 500 ml aerosol spray

**General**

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

**Disposal**

All used and unused product should be disposed of in accordance with state regulations.

**Shelf Life**

24 months from date of manufacture in sealed condition

**Handling**

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

**Limited Warranty**

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA

Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com

MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals.

© Registered trademark of ASV Multichemie Private Limited, INDIA.

THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Distributed by: