



RNC 10

Corrosion Inhibiting Wax Coating

Product Description

ASV® RNC 10 is a thin dry waxy film type corrosion inhibitor for providing short-term protection from rust and corrosion for up to 9 months indoors under normal storage conditions. It forms a light protective film over the surface and seals out entry of moisture & corrosion. Its dry non-staining formulation resists dirt & dust build up and is safe for use on all metals.

ASV® RNC 10 does not contain any CFCs or any ozone depleting substances.

Applications

Corrosion Protection for metal parts in storage, manufacture, shipping or in service as:

- Dies
- Jigs
- Tools
- Molds
- Instruments
- Solenoids
- Welds
- Castings
- Shafts
- Motors
- Spare Parts
- Freshly Machined Surfaces

Benefits

- Thin dry film provides short term corrosion protection for up to 9 months indoor storage conditions
- Ultrathin film provides mild lubrication
- Stops further rusting
- Penetrates into minutest cracks to stop further moisture ingress
- Removal of the film is not necessary
- Does not attract dirt & dust

Directions for Use - Bulk

Apply onto clean, dry and degreased surfaces by means of brush or by dipping components into the fluid. Ensure removal of rust, loose scales, dirt, dust and trapped moisture from surfaces before application. Mask areas not required to be coated. Apply uniformly a light film for maximum coverage. Two light films are better than a single thick film. For thicker films, recoat only after previous coat dries. Reuse as required.

Directions for Use - Aerosol

Shake can till bearing noise from inside is audible. Spray liberally, a light and even film onto the surface. Spray on to clean and degreased surface and remove dirt, rust, scales, dust and entrapped moisture prior to application of this product. Allow solvents to evaporate and film to dry before recoating. Reuse as required.

Caution

Contains flammable propellant and solvents. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

Technical Information

RNC 10

Corrosion Inhibiting Wax Coating

Technical Properties

| Property | Value | Value |
|-----------------------------|---|---|
| | Aerosol | Bulk |
| Type | Synthetic wax based corrosion inhibitor | Synthetic wax based corrosion inhibitor |
| Appearance | Liquid | Liquid |
| Color | Clear | Clear |
| Odor | Mild | Mild |
| Specific Gravity @ 20°C | 0.75 - 0.85 gm/cc | 0.75 - 0.85 gm/cc |
| Flash Point (Solvent) | -18°C (aerosol) | 60°C |
| Type of Film | Thin, dry waxy | Thin, dry waxy |
| Drying Time (RT) | 45-60 mins | 45-60 mins |
| Film Thickness | 0.05 mm | 0.05 mm |
| Optimum Film Thickness | 0.2- 0.5 mm | 0.2- 0.5 mm |
| Service Temperature Range | -40°C to +70°C | -40°C to +70°C |
| Solubility | Nil in water | Nil in water |
| Salt Spray Test (2.5mm DFT) | > 1000 hrs | > 1000 hrs |
| Coverage | 2-3 m ² /can | 10-14 m ² / liter |
| Corrosion Protection | Indoors | Indoors |
| Suitable For | All metals | All metals |
| Propellant | Non CFC | NA |

* of active ingredients

Available Packaging

- 500 ml aerosol spray
- 4 kg container

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Shelf Life

Bulk - 12 months from date of manufacture in sealed condition
 Aerosol - 24 months from date of manufacture

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA

Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com

MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals.

® Registered trademark of ASV Multichemie Private Limited, INDIA.

THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Distributed by: