



Battery Coating (Dry)

Corrosion Inhibitor for Protection of Battery Terminals

Product

Battery Coating (Dry) is a fast air-drying coating designed for protection of battery terminals from failure caused due to corrosion. It helps optimize the battery's performance level by providing a dry, tough, durable corrosion resistant protective coating which seals out battery acids, moisture, dirt, grease, oil and other contaminants that corrode and destroy metal contacts. Its blue color (or yellow if specified as color of choice) aids visual inspection of film.

Applications

It is effective for protection of battery terminals, clamps in all types of automobile, industrial, aircraft and marine batteries.

Benefits

- Prolongs battery life
- Prevents hard starting, current loss, and battery failure
- Maximizes performance and reliability
- Offers long lasting protection
- Dries quickly and protects instantly
- Resistant to water
- Red color provides easy visual inspection
- Contains no ozone depleting chemicals

Directions for Use

Shake can well before use. Repeat the same before every application. Remove existing residues with ASV® Battery Cleaner. Spray 8 to 10 inches from the surface in short dusting strokes. Apply successive coats within 10 minutes if needed. Do not wipe off. Reapply regularly for optimum battery life. To prevent clogging, turn can upside down and spray for 2 to 3 seconds until only propellant comes out. Prevent aerosol can contact with the battery terminals.

Caution

Contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

Technical Information

Battery Coating (Dry)

Technical Properties

Property	Value
Type	Paint like coating
Color	Blue (red or yellow as required)
Odor	Solvent
Appearance	Glossy
Specific Gravity @ 20°C	< 1.00 gm/cc
Flash Point	-18°C (aerosol)
Drying Time Schedule, @ 25°C	
- To Touch	5-10 mins
- To Handle	20-30 mins
Vapor Pressure (air =1)	> air
Coverage	2-3 m ² /can
Propellant	Non CFC

* of active ingredients

Available Packaging

- 500 ml aerosol spray

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Shelf Life

24 months from date of manufacture in sealed condition

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA

Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com

MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals.

® Registered trademark of ASV Multichemie Private Limited, INDIA.

THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Distributed by: