



Technical Information

Belt Dressing

Synthetic Lubricant

Anti Slippage & Synthetic Belt Conditioning Agent for All Types of Belts

Product Description

ASV® Belt Dressing is a non-staining, high tack, water resistant, synthetic lubricant cum belt conditioning treatment for improving grippage and preventing belt slippage for all flat, round and V-belts. It improves traction, prevents premature belt wearing off and eliminates belt squeaking or squealing noises. It conditions worn belts, maintains their flexibility and resilience to hardness while reducing slippage, cracking and glazing.

Applications

For use on all round, flat & V-belts in fans, pumps, machines, conveyors, air conditioners, textile machines, compressors, generators in all industrial machinery, conveyor systems, motorized equipment and vehicles.

Benefits

- Eliminates belt squeaking or squealing noises
- Provides for better operating efficiency
- Prevents hardening, glazing and premature cracking
- Increases life and tensile strength of belts
- Reduces energy loss through effective power transfer
- Maintains flexibility and resilience of belts

Directions for Use

Switch off the power and turn off the equipment before spraying this product. Protective guards or covers may have to be removed in some instances. Replace guards after application. Spray from a distance of 6-8 inches a light, even film on the stationary inner surface of belt in contact with pulleys from both the sides. Spray enough only to cover the length of the belt. Allow few minutes for the solvents to evaporate before restarting the equipment. Reapply occasionally to maintain full power and to optimize belt life. Not for use on timing or serpentine belts.

Caution

Contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

Technical Information

Belt Dressing

Synthetic Lubricant

Technical Properties

Property	Value
Type	Synthetic lubricant
Appearance	Tacky oil
Color	Colorless
Odor	Solvent
Base	Synthetic lubricant
Temperature Range °C	Up to +250
Vapor Pressure (air = 1)	> air
Evaporation rate	< n-butyl acetate
Solubility	Nil in water
Propellant	Non CFC

* of active ingredients

Available Packaging

- 500 ml aerosol spray

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Shelf Life

24 months from date of manufacture in sealed condition

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA

Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com

MOLYSULF® & ASV® Specialty Lubricants & MRO Technical Chemicals.

® Registered trademark of ASV Multichemie Private Limited, INDIA.

THIS PRODUCT IS DEVELOPED AND MANUFACTURED BY US FOR INDUSTRIAL USE ONLY.

Distributed by: