

LCG SERIES

GREASES

High Performance Premium Lithium Complex Soap Based Greases For Lubrication Of Bearings At High Temperatures

Product

ASV LCG grease series are mineral oil thickened with a premium lithium complex thickener and special additive combinations to provide excellent protection against wear, rust and corrosion. These high performance greases are designed for providing effective lubrication under conditions of temperatures, loads, shear forces and harsh environments. These greases exhibit excellent adhesion, shear stability and very good resistance to water.

Premium additives used for enhancing extreme pressure properties demonstrate high load and wear reducing capabilities to make these greases ideal for use under demanding conditions.

ASV LCG series of greases provide extended lubrication, increase equipment wear life, reduce energy consumption, maintenance costs, downtime and are ideally suited for lubrication of bearings subjected to heavy loads, slow to medium speeds and high temperatures.

Applications

For roller and plain bearings in steel, mining, cement, construction, textile, paper, heavy engineering industry.

Benefits

- Extremely wide service temperature range of -20°C to +160°C
- Excellent resistance to water
- Extend re-lubrication intervals and cut down lubricant consumption
- Combination of EP additives increase the load bearing capacity
- Offer good surface protection and corrosion inhibiting properties
- Very good shear stability under moderate to high loads and medium speeds
- Make sliding smoother and reduce operational noise
- Increase wear life of the equipment
- Good resistance to oxidation and corrosion

Directions for Use

Use as supplied. Never dilute or mix with other oil or grease. Apply on all clean sliding surfaces by normal greasing methods i.e. by brush, grease gun or dispense via centralized lubrication systems.

LCG SERIES

GREASES

TECHNICAL PROPERTY						
PARAMETER	VALUE				UNIT	STANDARD
	Product	LCG 100	LCG 220 B	LCG 460		
Appearance	Smooth grease	Smooth grease	Smooth grease	Smooth grease		Visual
Color	Brown	Blue	Brown	Brown		Visual
Base oil	Mineral	Mineral	Mineral	Mineral		In house
Base oil viscosity @ 40°C	~ 100	~ 220	~ 460	~ 1000	mm ² /s	ASTM D 445
Thickener	Lithium complex	Lithium complex	Lithium complex	Lithium complex		In house
Penetration, worked	265-295	265-295	265-295	250-275	mm/10	ASTM D 217
NLGI consistency	2	2	2	2	Class	DIN 51 818
Drop point	+ 230	+ 280	+ 280	+ 280	°C	ASTM D 2265
Copper strip corrosion	1a	1a	1a	1a	Rating	ASTM D 4048
Rust prevention	Pass	Pass	Pass	Pass		ASTM D 1743
Water washout	< 3	< 3	< 2	< 2	%	ASTB D 1264
Four ball test, weld load	280	315	400	800	kg	ASTM D 2596
Four ball test, scar dia.	0.5	0.5	0.5	0.5	mm	ASTM D 2266
Service temperatures	-20 to +150	-20 to +160	-20 to +160	-20 to +160	°C	

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Available Packaging

5 kg, 20 kg, 180 kg

Shelf Life

36 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE
PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.