



Cleans effectively gum & varnish from throttle plates & air intake system

Helps correct rough idling & stalling problems

Improves efficiency, economy & power

Throttle Body & Air Intake Cleaner

ASV® Throttle Body & Air Intake Cleaner is a blend of powerful cleaning solvents specifically designed to clean, dissolve and remove performance inhibiting residues like gum, dirt, dust, sludge and varnish deposits.

ASV® Throttle Body & Air Intake Cleaner helps clean and free sticky valves, heat risers and throttle linkages.

Effective cleaning and removal of contaminants maximizes performance while improving fuel system efficiency thereby ensuring and maximizing fuel economy.

Appearance	Color	Туре	Flash Point, °C	Specific Gravity, Active Contents	Evaporation Rate	Residue On Evaporation	Propellant
Clear Liquid	Colorless	Non chlorinated	<-17C	0.80 g/cc	Very Fast	None	Carbon Dioxide

Available Packaging

- 500 ml aerosol spray

Shelf Life

24 months from date of manufacture in sealed condition

PROFESSIONAL STRENGTH AUTOMOTIVE MAINTENANCE SOLUTIONS



Directions for use

Keep away from electrical connections and battery terminals. NOT FOR USE ON vehicles fitted with super or turbo chargers or diesel engines. DO NOT use on painted surfaces or sensitive plastics. DO NOT spray through air filter or mass air flow sensor.

Turn off the engine and remove air induction hose from throttle body. It may be necessary to remove the mass air flow sensor.

Place a shop rag/cloth under the throttle body to soak the spent runoff and dissolved deposits.

With throttle in wide open position, spray liberally on both sides of throttle plate, ports and surrounding air intake area. DO NOT spray continuously.

Clean throttle parts and linkages completely with a clean shop cloth.

Re-install mass air flow sensor, air induction hose and filter.

Note: If spilled or sprayed on painted surface, wipe off or wash off immediately as paint may be affected.

Caution: Contents under pressure. Do not puncture, pierce or incinerate the container, even after use. Protect from sunlight and store away from heat and sources of ignition. Do not use on energized equipment or on live circuits. Do not expose to temperatures exceeding 50°C (120°F). Use only in well ventilated areas. As this can conducts electricity, prevent the risk of electrical shock by keeping away from all live electrical connections and sources of electricity. Do not breathe vapors or spray mist. Harmful by inhalation and avoid contact with skin and eyes. In case of eye contact, flush eyes with water and contact a physician. If swallowed, may be harmful or fatal. DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. KEEP OUT OF REACH OF CHILDREN. Dispose as industrial waste only in accordance with governing regulations. For proper disposal empty aerosol can completely.

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safety, short and long term exposure, physical and health hazards and is available from ASV or your local ASV distributor.

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User

is responsible for determining whether recommended ASV® product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.

ASV[®] is a leading pioneer in the production of specialized lubricants and technical chemicals in India for the MRO industry for nearly 5 decades.

Founded in 1969 with the introduction of Molysulf® line of solid film lubricants for tribological applications, today ASV® manufactures a broad range of products for diversified industrial needs as lubrication, cleaning and protection by way of performance oriented cost benefitting solutions.

Contact us today to discover how you can increase productivity as well as increase equipment performance while reducing maintenance and operational costs.

ASV MULTICHEMIE PRIVATE LIMITED

Registered Office & Works: W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai-400 701, INDIA
Tel: +91 (022) 2764 2514 | E-mail: info@asvmultichemie.com
MOLYSULF® ASV® Specialty Lubricants & MRO Technical Chemicals
® Registered trademark of ASV Multichemie Private Limited, INDIA

