

SuperWeld

J-B Weld Company LLC

Version No: 4.5

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **04/19/2023** Print Date: **07/27/2023** S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	SuperWeld
Chemical Name	ethyl cyanoacrylate
Synonyms	33102, 33106 SuperWeld
Chemical formula	Not Applicable
Other means of identification	UFI:89PX-G28T-S00R-9J11

Recommended use of the chemical and restrictions on use

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	J-B Weld Company LLC	J-B Weld Company, LLC
Address	400 CMH Road TX 75482 United States	400 CMH Road Sulphur Springs, TX 75482 United States
Telephone	903-885-7696	903-885-7696
Fax	Not Available	Not Available
Website	WWW.JBWeld.com	www.JBWeld.com
Email	info@JBWeld.com	info@jbweld.com

Emergency phone number

Association / Organisation	InfoTrac	InfoTrac
Emergency telephone numbers	Transportation Emergencies: 800-535-5053 or (24 hours)	Transportation Emergencies 01-800-681-1530 (24 hour)
Other emergency telephone numbers	Poison Control Centers: Medical Emergencies 800-222-1222 (24 hours)	Not Available

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Skin Corrosion/Irritation Category 2

Label elements

Hazard pictogram(s)



Signal word

Warning

lazard statement(s)

nazaru statement(s)	
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Version No: 4.5

Page 2 of 8

SuperWeld

Issue Date: **04/19/2023**Print Date: **07/27/2023**

H315

Causes skin irritation

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing mist/vapours/spray.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P362	Take off contaminated clothing and wash before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P332+P313	If skin irritation occurs: Get medical advice/attention.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7085-85-0	100	ethyl cyanoacrylate

SECTION 4 First-aid measures

Description of first aid measures

Eyelid Adhesion

- Wash thoroughly with water and apply moist pad; maintain in position.
- DO NOT force separation.
- ► Transport to hospital, or doctor without delay.
- Minor eye contamination should be treated by copious washing with water or 1% sodium carbonate solution.
 The eye will generally open without further action, typically in one to two days. there should be no residual damage.
- The eye will generally openAdhesive introduced
- Removal of contact lenses after eye injury should only be undertaken by skilled personnel.

Adhesive in the Eye:

- Adhesive will attach itself to eye proteins and will disassociate from these over intermittent periods, usually within several hours.
- ▶ This will result in weeping until clearance of the protein complex.
- It is important to understand that disassociation will normally occur within a matter of hours even with gross contamination.

Skin Contact:

involving cyanoacrylates are best handled by passive, non-surgical first aid.

Skin Contact:

- ▶ Remove excessive adhesive.
- Soak in warm water the adhesive should loosen from the skin in several hours. Dried adhesive does not present a health hazard.
- Contact with clothes, fabric, rags or tissues may generate heat, and strong irritating odours; skin burns may also ensue.

Skin Contact

Eve Contact

- Skin Adhesion:

 IMMEDIATELY immerse affected areas in warm soapy water.
- DO NOT force bonded surfaces apart.
- Use a gentle rolling action to peel surfaces apart if possible. It may be necessary to use a blunt edge such as a spatula or spoon handle. Do NOT attempt to pull the surfaces apart with a direct opposing action.

Cyanoacrylate adhesives is a very fast setting and strong, they bond human tissues including skin in seconds. Experience shows that accidents

- Remove any cured material with warm, soapy water.
- ► Seek medical attention without delay.
- A solvent such as acetone may be used (with care!) to separate bonded skin surfaces. **NEVER** use solvent near eyes, mouth, cuts, or abrasions.

Inhalation

- If fumes, aerosols or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.
 If tumes or combustion products are inhale
- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.

Version No: 4.5 Page 3 of 8 Issue Date: 04/19/2023 Print Date: 07/27/2023

SuperWeld

	 Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. For material bonded in the mouth seek medical/dental attention. If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peal or roll lips apart. Do NOT attempt to pull the lips with direct opposing action. It is almost impossible to swallow cyanoacrylates. The adhesive solidifies and adheres in the mouth. Saliva will lip the adhesion in one or two days.

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

It should never be necessary to use surgical means to separate tissues which become accidentally bonded. The action of physiological fluids or warm soapy water will cause this adhesive to eventually fail.

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- ► Dry chemical powder.

Special hazards arising from the substrate or mixture

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result Fire Incompatibility

Special protective equipment and precautions for fire-fighters

Special protective equipment and precautions for fire-fighters	
Fire Fighting	 Alert Fire Department and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.
Fire/Explosion Hazard	► Combustible. ► Slight fire hazard when exposed to heat or flame. Combustion products include: , carbon dioxide (CO2) , nitrogen oxides (NOx) , other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	If cloth has been used to wipe up spills, immediately soak the cloth in water to produce polymerisation and prevent possibility of autoignition. Remove all ignition sources. Clean up all spills immediately.
Major Spills	Moderate hazard. • Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Frecautions for sale nationing		
	Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. DO NOT allow clothing wet with material to stay in contact with skin
	Other information	Store in original containers. Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

	Metal can or drum
Suitable container	Packaging as recommended by manufacturer.
	Check all containers are clearly labelled and free from le

Version No: 4.5

Page 4 of 8 SuperWeld

Issue Date: **04/19/2023** Print Date: **07/27/2023**

For cyanoacrylates:

- Avoid contact with acids, bases, amines.
 - Avoid contact with clothes, fabric, rags (especially cotton and wool) rubber or paper; contact may cause polymerisation.
 - Segregate from alcohol, water.
 - ► Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

Storage incompatibility

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
SuperWeld	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
ethyl cyanoacrylate	Not Available		Not Available	

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit		
ethyl cyanoacrylate	E ≤ 0.1 ppm			
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.			

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Individual protection measures, such as personal protective equipment	
Eye and face protection	 Safety glasses with side shields. Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Polyethylene gloves
Body protection	See Other protection below
Other protection	Overalls. P.V.C apron.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear Liquid				
Physical state	Liquid	Relative density (Water = 1)	1.05-1.10		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available		

Page 5 of 8

SuperWeld

Issue Date: **04/19/2023**Print Date: **07/27/2023**

	1		
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. In low humidity, cyanoacrylate vapours are irritating to the respiratory system and eyes. High concentrations may cause inflammation of the lungs and other complications. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence.
Ingestion	Uncured cyanoacrylates are difficult to swallow as saliva cures the surface of the adhesive with negligible bonding. The cured material is considered to be non-hazardous. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Small n-alkyl cyanoacrylates cause burns and irritation on skin contact. Exposure to their vapours can cause irritation, but usually only in dry conditions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons. Exposure to cyanoacrylate vapours can cause discomfort and tears, nasal discharge, and blurred vision. The eyelids may be glued shut.
Chronic	Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Dermatitis may result from prolonged exposures. On repeated and prolonged exposure by skin contact or inhalation, a small proportion of individuals develop allergic sensitivities. Chronic exposure to cyanides and certain nitriles may result in interference to iodine uptake by thyroid gland and its consequent enlargement. This occurs following metabolic conversion of the cyanide moiety to thiocyanate.

SuperWeld	TOXICITY	IRRITATION
	Not Available	Not Available
ethyl cyanoacrylate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 233.2 mg/kg ^[2]	Not Available
	Inhalation(Rat) LC50: 5.278 mg/L4h ^[2]	
	Oral (Rat) LD50: 190.8 mg/kg ^[2]	

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

ETHYL CYANOACRYLATE	
---------------------	--

* [AIHAAP]

SuperWeld & ETHYL CYANOACRYLATE

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. For methyl cyanoacrylate (MCA) and ethyl cyanoacrylate (ECA)

Studies show that the key toxicological features of MCA and ECA are as a result of local activity at the site of contact. Liquid MCA and ECA may cause eye and skin irritation on repeated exposure but inconclusive evidence of skin sensitization and asthma causing effect.

SuperWeld

Issue Date: **04/19/2023**Print Date: **07/27/2023**

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

– Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
SuperWeld	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
ethyl cyanoacrylate	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan - Bioconcentration Data 8. Vendor Data				

Substances containing unsaturated carbons are ubiquitous in indoor environments. They result from many sources (see below). **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethyl cyanoacrylate	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation	
ethyl cyanoacrylate	LOW (LogKOW = 1.4174)	

Mobility in soil

Ingredient	Mobility	
ethyl cyanoacrylate	LOW (KOC = 6.847)	

SECTION 13 Disposal considerations

Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.

SECTION 14 Transport information

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as Dangerous Goods in Excepted Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethyl cyanoacrylate	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type

Version No: 4.5

Page 7 of 8

SuperWeld

Issue Date: **04/19/2023**Print Date: **07/27/2023**

Product name	Ship Type
ethyl cyanoacrylate	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

ethyl cyanoacrylate is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No
No
Yes
No
Yes
No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65

None Reported

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (ethyl cyanoacrylate)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

Version No: 4.5 Page 8 of 8 Issue Date: 04/19/2023 Print Date: 07/27/2023

SuperWeld

SECTION 16 Other information

Revision Date	04/19/2023
Initial Date	11/15/2020

SDS Version Summary

Version	Date of Update	Sections Updated
3.5	04/18/2023	Identification of the substance / mixture and of the company / undertaking - Supplier Information

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or

Powered by AuthorITe, from Chemwatch.