# **S** Permatex

### SAFETY DATA SHEET

Revision Date 10-Apr-2015

Version 1

### 1. IDENTIFICATION

Product identifier

Product Name DEVCON HOME PLASTIC WELDER (ADHESIVE)

Other means of identification

Product Code 22045 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Distributor

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

### 2. HAZARDS IDENTIFICATION

### Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2 Sub-category A
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Flammable liquids	Category 2

### Label elements

Emer	ge	ncy	O١	/er	view

### Danger

Harmful if swallowed Causes skin irritation May cause an allergic skin reaction

Causes serious eye irritation
Highly flammable liquid and vapor



Appearance White

Physical state Viscous liquid

**Odor** Solvent

### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

### **Precautionary Statements - Response**

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool

### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)\_

Not applicable

### Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

17.5% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
METHYL METHACRYLATE	80-62-6	30 - 60	•
METHACRYLIC ACID	79-41-4	5 - 10	•
TETRASODIUM EDTA	64-02-8	3 - 7	*
P-TOLUENESULFONYL CHLORIDE	98-59-9	3 - 7	*
ETHOXYLATED TRIMETHYLOLPROPANE TRIACRYLATE	28961-43-5	3 - 7	*
DIMETHYLBENZYL HYDROPEROXIDE	80-15-9	3-7	*
BUTYLATED HYDROXY TOLUENE	128-37-0	3-7	*
ACRYLONITRILE-BUTADIENE POLYMER	9003-18-3	3-7	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

### Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact tenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

### Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

### Indication of any immediate medical attention and special treatment needed

### 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

### Unsuitable extinguishing media

None.

### Specific hazards arising from the chemical

Highly flammable.

Explosion data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### **6. ACCIDENTAL RELEASE MEASURES**

### Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

Inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Take precautionary measures against static discharges. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

### Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a well-ventilated place. Keep cool. Do not expose to temperatures exceeding 50

°C/122 °F.

Incompatible materials Strong oxidizing agents, Reducing agent

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL METHACRYLATE	STEL: 100 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	IDLH: 1000 ppm TWA: 100 ppm
80-62-6	TWA: 50 ppm	(vacated) TWA: 410 mg/m³ (vacated) TWA: 410 mg/m³	TWA: 410 mg/m <sup>3</sup>
METHACRYLIC ACID 79-41-4	TWA: 20 ppm	(vacated) TWA: 20 ppm (vacated) TWA: 70 mg/m³ (vacated) S*	TWA: 20 ppm TWA: 70 mg/m³
BUTYLATED HYDROXY TOLUENE 128-37-0	TWA: 2 mg/m³ inhalable fraction and vapor	(vacated) TWA: 10 mg/m³	TWA: 10 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eyelface protection Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

**General Hygiene Considerations** 

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

Remarks · Method

Butyl acetate = 1

Air = 1

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state **Appearance** Odor Odor threshold

Viscous liquid White Solvent 0.75 ppm

Property

pΗ Melting point / freezing point Boiling point / boiling range

Flash point **Evaporation rate** 

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density

Relative density Water solubility

Solubility in other solvents Partition coefficient Autoignition temperature

**Decomposition temperature** Kinematic viscosity Dynamic viscosity **Explosive properties Oxidizing properties** 

Values Not applicable

No information available 100 °C / 212 °F 12 °C / 53 °F > 1

No information available

No information available No information available 28 mmHg @ 68°F

>3 0.95

Slightly soluble

No information available No information available 421°C (789.8°F) No information available

No information available No information available No information available No information available

### Other Information

Softening point Molecular weight VOC Content (%)

Density **Bulk density** 

No information available No information available

<50 g/L

No information available No information available

### 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### **Chemical stability**

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to\_avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents, Reducing agent

**Hazardous Decomposition Products** 

Carbon oxides

Nitrogen oxides (NOx)

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL METHACRYLATE 80-62-6	= 7872 mg/kg (Rat) = 7900 mg/kg (Rat)	> 5 g/kg(Rabbit)	= 4632 ppm (Rat)4 h
METHACRYLIC ACID 79-41-4	= 1060 mg/kg (Rat)	500 - 1000 mg/kg (Rabbit) = 500 mg/kg (Rabbit)	= 7.1 mg/L (Rat) 4 h
TETRASODIUM EDTA 84-02-8	= 10 g/kg (Rat) = 1658 mg/kg ( Rat)	•	-
ETHOXYLATED FRIMETHYLOLPROPANE FRIACRYLATE 28961-43-5	•	> 13 g/kg(Rabbit)	•
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	= 382 mg/kg (Rat)	= 0.126 mL/kg ( Rabbit )	= 220 ppm (Rat)4h
BUTYLATED HYDROXY FOLUENE 128-37-0	= 890 mg/kg (Rat)	> 2000 mg/kg (Rat)	•

### Information on toxicological effects\_

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

outoniogernoity	1110 (0010 001	OTT III GIOGROS TITIORITO COOL	ragority mad noted any me	rodionit do di adroniogoni.
Chemical Name	ACGIH	IARC	NTP	OSHA
METHYL METHACRYLATE : 80-62-6	•	Group 3	-	-
BUTYLATED HYDROXY TOLUENE 128-37-0	-	Group 3	<u>.</u>	-

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Target Organ Effects Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1929 mg/kg
ATEmix (dermal) 3269 mg/kg
ATEmix (inhalation-dust/mist) 8.3 mg/l
ATEmix (inhalation-vapor) 6948 mg/l

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity\_**

30% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
METHYL METHACRYLATE 80-62-6	170: 96 h Pseudokirchneriella subcapitata mg/L EC50	243 - 275: 96 h Pimephales promelas mg/L LC50 flow-through 170 - 206: 96 h Lepomis macrochirus mg/L LC50 flow-through 153.9 - 341.8: 96 h Lepomis macrochirus mg/L LC50 static 79: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 79: 96 h Oncorhynchus mykiss mg/L LC50 static 125.5 - 190.7: 96 h Pimephales promelas mg/L LC50 static 326.4 - 426.9: 96 h Poecilla reticulata mg/L LC50 static	69: 48 h Daphnia magna mg/L EC50
TETRASODIUM EDTA 64-02-8	1.01: 72 h Desmodesmus subspicatus mg/L EC50	41: 96 h Lepomis macrochirus mg/L LC50 static 59.8: 96 h Pimephales promelas mg/L LC50 static	610: 24 h Daphnia magna mg/L EC50
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	•	3.9: 96 h Oncorhynchus mykiss mg/L LC50 static	7: 24 h Daphnia magna mg/L EC50
BUTYLATED HYDROXY TOLUENE 128-37-0	6: 72 h Pseudokirchneriella subcapitata mg/L EC50 0.42: 72 h Desmodesmus subspicatus mg/L EC50	5: 48 h Oryzias latipes mg/L LC50	

### Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

### **Mobility**

No information available.

Chemical Name	Partition coefficient
METHYL METHACRYLATE 80-62-6	0.7
METHACRYLIC ACID 79-41-4	0.93
BUTYLATED HYDROXY TOLUENE 128-37-0	4.17

### Other adverse effects

No information available

### 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging

Do not reuse container.

**US EPA Waste Number** 

D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL METHACRYLATE 80-62-6	U162	Included in waste stream: F039	•	U162
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	-		-	U096

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL METHACRYLATE	Toxic
80-62-6	Ignitable
DIMETHYLBENZYL HYDROPEROXIDE	Toxic
80-15-9	Ignitable

### 14. TRANSPORT INFORMATION

DOT

<u>UN/ID no</u> 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group II
Emergency Response Guide 128

Number

IATA

<u>UN/ID no</u> ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

**IMDG** 

**UN/ID no** 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group II
EmS-No F-E, S-D

### 15. REGULATORY INFORMATION

International Inventories

Complies **TSCA** Complies **DSL/NDSL** Not Listed. **EINECS/ELINCS ENCS** Not Listed. Complies **IECSC** Complies **KECL** Complies **PICCS** AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

# 22045 - DEVCON HOME PLASTIC WELDER (ADHESIVE)

Chemical NameSARA 313 - Threshold Values %METHYL METHACRYLATE - 80-62-61.0DIMETHYLBENZYL HYDROPEROXIDE - 80-15-91.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

**CWA (Clean Water Act)** 

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantitles	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
METHYL METHACRYLATE 80-62-6	1000 lb	-	-	х

### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHYL METHACRYLATE	1000 lb	•	RQ 1000 lb final RQ
80-62-6			RQ 454 kg final RQ
DIMETHYLBENZYL	10 lb	-	RQ 10 lb final RQ
HYDROPEROXIDE			RQ 4.54 kg final RQ
80-15-9			1

### **US State Regulations**

### California Proposition 65

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
METHYL METHACRYLATE 80-62-6	X	×	Х
METHACRYLIC ACID 79-41-4	X	×	Х
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	x	×	×
BUTYLATED HYDROXY TOLUENE 128-37-0	X	×	×

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA Health hazards 2 Flammability 3 Instability 0 - Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 10-Apr-2015

<u>Disclaimer</u>
The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

### SAFETY DATA SHEET

Revision Date 10-Apr-2015

Version 1

### 1. IDENTIFICATION

Product identifier

**Product Name** 

DEVCON HOME PLASTIC WELDER (ACTIVATOR)

Other means of identification

**Product Code** 

22045V

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use

Activator

Uses advised against

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

**Distributor** 

**ITW Permatex** 

ITW Permatex Canada

10 Columbus Blvd.

35 Brownridge Road, Unit 1

Hartford, CT 06106 USA

Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number

1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency:

00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address

mail@permatex.com

### 2. HAZARDS IDENTIFICATION

### Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Skin sensitization	Category 1
Flammable liquids	Category 2

### Label elements

Emergency	Overvi	ew

### Danger

Harmful if swallowed Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction May cause respiratory irritation

Highly flammable liquid and vapor



Appearance White

Physical state Viscous liquid

Odor Solvent

### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Use only non-sparking tools

Take precautionary measures against static discharge

### Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

### Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

### Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

20% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
METHYL METHACRYLATE	80-62-6	60 - 100	*
ACRYLONITRILE-BUTADIENE POLYMER	9003-18-3	3 - 7	*
3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPY LPYRIDINE	34562-31-7	3 - 7	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

If SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Highly flammable.

Explosion data

Sensitivity to Mechanical Impact

Sensitivity to Static Discharge

None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Remove all sources of ignition. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** 

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials

Strong oxidizing agents, Reducing agent

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL METHACRYLATE	STEL: 100 ppm	TWA: 100 ppm	IDLH: 1000 ppm
80-62-6	TWA: 50 ppm	TWA: 410 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 410 mg/m <sup>3</sup>
		(vacated) TWA: 410 mg/m <sup>3</sup>	· ·

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

**Engineering Controls** 

Showers

Eyewash stations Ventilation systems

### Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state Viscous liquid Appearance White Odor Solvent Odor threshold 0.75 ppm

Property Values Remarks • Method PH Not applicable

Melting point / freezing point

No information available

Boiling point / boiling range

No information available

101 °C / 213 °F

Flash point 12 °C / 53 °F Tag Closed Cup Evaporation rate >1 Butyl acetate = 1

Air = 1

Flammability (solid, gas) No information available

Flammability Limit in Air
Upper flammability limit: 12.5%

Lower flammability limit: 1.6% Vapor pressure 28 mmHg @ 68°F

Vapor density >3
Relative density 0.95

Water solubility Slightly soluble

Solubility in other solvents

Partition coefficient
Autoignition temperature

No information available 421°C (789.8°F)

Decomposition temperature
Kinematic viscosity
No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) <50 g/L

DensityNo information availableBulk densityNo information available

### 10. STABILITY AND REACTIVITY

Reactivity

No data available

**Chemical stability** 

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

**Conditions to avoid** 

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Reducing agent

**Hazardous Decomposition Products** 

Carbon oxides

Nitrogen oxides (NOx)

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion

Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL METHACRYLATE	= 7872 mg/kg (Rat) = 7900 mg/kg	> 5 g/kg (Rabbit)	= 4632 ppm (Rat) 4 h
80-62-6	(Rat)		

### Information on toxicological effects

**Symptoms** 

No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure\_

Sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
METHYL METHACRYLATE	•	Group 3	-	-
80-62-6				

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Target Organ Effects

Eyes, Respiratory system, Skin.

### The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 7872 mg/kg

 ATEmix (dermal)
 5005 mg/kg

 ATEmix (inhalation-vapor)
 4632 mg/l

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

20% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
METHYL METHACRYLATE	170: 96 h Pseudokirchneriella	243 - 275: 96 h Pimephales	69: 48 h Daphnia magna mg/L
80-62-6	subcapitata mg/L EC50	promelas mg/L LC50 flow-through	EC50
		170 - 206: 96 h Lepomis	
		macrochirus mg/L LC50	
		flow-through 153.9 - 341.8: 96 h	
		Lepomis macrochirus mg/L LC50	
		static 79: 96 h Oncorhynchus	
		mykiss mg/L LC50 flow-through 79:	
		96 h Oncorhynchus mykiss mg/L	
		LC50 static 125.5 - 190.7: 96 h	
		Pirnephales prometas mg/L LC50	
		static 326.4 - 426.9: 96 h Poecilia	
		reticulata mg/L LC50 static	

### Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

### 22045V - DEVCON HOME PLASTIC WELDER (ACTIVATOR)

**Mobility** 

No information available.

Chemical Name	Partition coefficient
METHYL METHACRYLATE	0.7
80-62-6	

### Other adverse effects

No information available

### 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL METHACRYLATE	U162	Included in waste stream:	- '	U162
80-62-6		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL METHACRYLATE	Toxic
80-62-6	<u>Ignitable</u>

### 14. TRANSPORT INFORMATION

DOT

UN/ID no 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group II
Emergency Response Guide 128

Number

**IATA** 

UN/ID no ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

**IMDG** 

UN/ID no 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group II
EmS-No F-E, S-D

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

### 22045V - DEVCON HOME PLASTIC WELDER (ACTIVATOR)

EINECS/ELINCS Not Listed.
ENCS Not Listed.
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL - Korean Existing and Evaluated Chemical Substances** 

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### US Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
METHYL METHACRYLATE - 80-62-6	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantitles	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
METHYL METHACRYLATE 80-62-6	1000 lb	•	•	Х

### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHYL METHACRYLATE	1000 lb	-	RQ 1000 lb final RQ
80-62-6			RQ 454 kg final RQ

### **US State Regulations**

### California Proposition 65

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
METHYL METHACRYLATE	X	×	X
80-62-6			

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

## 22045V - DEVCON HOME PLASTIC WELDER (ACTIVATOR)

Revision Date 10-Apr-2015

NFPA HMIS Health hazards 2 Health hazards 2 Flammability 3 Flammability 3

Instability 0 Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

**Revision Date** 

10-Apr-2015

### **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**