

## SAFETY DATA SHEET

## CalCheck D-2 - Aerosol

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## Trade name

CalCheck D-2 - Aerosol

## Product no.

1562/400

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Relevant identified uses of the substance or mixture

Industrial purposes

Restricted to professional users.

## Uses advised against

None known.

## 1.3. Details of the supplier of the safety data sheet

## Company and address

**Callington (Thailand) Co., Ltd.**

26/80 (A12) Moo.7, Rachathewa, Bangplee

10540 Samut Prakarn

Thailand

+66(0)2 098 8288

www.callington.com

## E-mail

thailand@callington.com

## SDS date

1/4/2025

## SDS Version

4.0

## Date of previous version

27/8/2024 (3.0)

## 1.4. Emergency telephone number

In an emergency call 000

In less severe situations call the Poisons Information Centre: 13 11 26 (Available 24/7 from anywhere in Australia)

See section 4 "First aid measures".

## SECTION 2: Hazards identification

This material is considered hazardous according to the Work Health and Safety Regulations.

## 2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

## 2.2. Label elements

## Hazard pictogram(s)



## Signal word

Danger

## Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Causes serious eye irritation. (H319)

May cause drowsiness or dizziness. (H336)

**Precautionary statement(s)**

**General**

-

**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not pierce or burn, even after use. (P251)

Wear eye protection. (P280)

**Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. (P305+P351+P338)

If eye irritation persists: Get medical advice/attention. (P337+P313)

**Storage**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

**Disposal**

Dispose of contents/container in accordance with local regulation (P501)

**▼ Hazardous substances**

Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately – 40 °C to 80 °C (– 40 °F to 176 °F).]

propan-2-ol; isopropyl alcohol; isopropanol

acetone; propan-2-one; propanone

**Additional labelling**

Not applicable.

**2.3. Other hazards**

**Additional warnings**

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Not applicable. This product is a mixture.

**3.2. Mixtures**

Product/substance	Identifiers	% w/w	Classification	Note
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately – 40 °C to 80 °C (– 40 °F to 176 °F).]	CAS No.: 68476-85-7 EC No.: 270-704-2	30-60%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	[19]
propan-2-ol; isopropyl alcohol; isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7	30-60%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
acetone; propan-2-one; propanone	CAS No.: 67-64-1 EC No.: 200-662-2	10-30%	AUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In the case of accident: Contact a doctor or casualty department – bring the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

##### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

##### Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

##### Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

##### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

##### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

##### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure call the NSW Poisons Information Centre on 13 11 26 (Available 24/7) in order to obtain further advice.

Hazchem Code: None

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

**6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

**6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

**6.4. Reference to other sections**

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

**7.2. Conditions for safe storage, including any incompatibilities**

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

**Recommended storage material**

Keep only in original packaging.

**Storage conditions**

Dry, cool and well ventilated

**Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**7.3. Specific end use(s)**

This product should only be used for applications quoted in section 1.2.

**SECTION 8: Exposure controls/personal protection****8.1. ▼ Control parameters**

Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately - 40 °C to 80 °C (- 40 °F to 176 °F).]

Long term exposure limit (8 hours) (ppm): 1000

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1800

propan-2-ol; isopropyl alcohol; isopropanol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 983

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1230

acetone; propan-2-one; propanone

Long term exposure limit (8 hours) (ppm): 500

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1185

Short term exposure limit (15 minutes) (ppm): 1000  
 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 2375

Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)  
 Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 2.5

Magnesium carbonate  
 Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10

Workplace exposure standards for airborne contaminants (Safe Work Australia). (January 2024)

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

## Individual protection measures, such as personal protective equipment

### Generally

Use only protective equipment that carries the RCM symbol.

### Respiratory Equipment

No specific requirements

### Skin protection

No specific requirements.

### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
No special when used as intended	-	-	-

### Eye protection

No specific requirements.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Form

Aerosol

#### Colour

No data available

#### Odour

No data available

#### Odour threshold (ppm)

No data available

#### pH

No data available

#### Density (g/cm<sup>3</sup>)

No data available

#### Relative density

No data available

**Kinematic viscosity**

No data available

**Particle characteristics**

No data available

**Phase changes**

**Melting point/Freezing point (°C)**

No data available

**Softening point/range (°C)**

Does not apply to aerosols.

**Boiling point (°C)**

No data available

**Vapour pressure**

No data available

**Relative vapour density**

No data available

**Decomposition temperature (°C)**

No data available

**Data on fire and explosion hazards**

**Flash point (°C)**

No data available

**Flammability (°C)**

The material is ignitable.

**Auto-ignition temperature (°C)**

No data available

**Explosion limits (% v/v)**

No data available

**Solubility**

**Solubility in water**

No data available

**n-octanol/water coefficient (LogKow)**

No data available

**Solubility in fat (g/L)**

No data available

**9.2. Other information**

**Evaporation rate (n-butylacetate = 100)**

No data available

**Other physical and chemical parameters**

No data available.

**Oxidizing properties**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

The product is stable under the conditions, noted in section 7 "Handling and storage".

**10.3. Possibility of hazardous reactions**

None known.

**10.4. Conditions to avoid**

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

Extremes of temperature

Storage in the open is not recommended.

**10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**10.6. ▼ Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) has been classified by IARC as a group 3 carcinogen.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

## SECTION 12: Ecological information

### 12.1. Toxicity

No data available.

### 12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

### 12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

### 12.6. Other adverse effects

None known.

## SECTION 13: Disposal considerations

### Waste treatment methods

Dispose of contents/container to an approved waste disposal plant.

### Specific labelling

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information .
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information .
IATA	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information .

\* Packing group

\*\* Environmental hazards

### ▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: None

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

No specific requirements.

#### Control of major hazard facilities

Not applicable.

#### Additional information

Not applicable.

#### The Australian Inventory of Industrial Chemicals (AIIC)

Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately - 40 °C to 80 °C (- 40 °F to 176 °F).] is listed

propan-2-ol; isopropyl alcohol; isopropanol is listed

acetone; propan-2-one; propanone is listed

Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) is listed

Magnesium carbonate is listed

#### Sources

Model Work Health and Safety Regulations as at 1 January 2021.

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

AUH066, Repeated exposure may cause skin dryness or cracking.

H220, Extremely flammable gas.

H225, Highly flammable liquid and vapour.

H280, Contains gas under pressure; may explode if heated.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

#### The full text of identified uses as mentioned in section 1

None known.

#### Abbreviations and acronyms

ADG = The Australian Code for the Transport of Dangerous Goods by Road & Rail

AICIS = Australian Industrial Chemicals Introduction Scheme

AIIC = Australian Inventory of Industrial Chemicals

AS = Australian Standard

AS/NZS = Australian New Zealand Standard

ATE = Acute Toxicity Estimate

AUH = Hazard statements specific for Australia

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

EINECS = European Inventory of Existing Commercial chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

Hazchem = Hazardous chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NICNAS = National Industrial Chemicals Notification and Assessment Scheme (replaced by AICIS since 2020)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

RCM = Regulatory Mark of Conformity

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

SCL = A specific concentration limit

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

SUSMP = Standard for the Uniform Scheduling of Medicines and Poisons

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

WHS = Work Health and Safety Regulations

#### Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by the Work Health and Safety Regulations.

The classification of the mixture in regard to physical hazards has been based on experimental data.

#### The safety data sheet is validated by

JG

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: AU-en